



**CLEANROOM MANAGEMENT INTERNATIONAL**

*We care for your compliance*

Data sheet  
testo 176 P1

Be sure. **testo**

# Data logger

## Pressure, temperature and humidity

testo 176 P1



---

High level of data security

---

Internal absolute pressure sensor and connection possibility for two external temperature/humidity probes

---

Parallel temperature/humidity measurement at two sites

---

Measurement data memory 2 million measurement values

---

Up to 8 years' battery life

---

Data transfer via USB cable or SD card

---

hPa

°C

%RH

td

g/m<sup>3</sup>

inch  
H<sub>2</sub>O



IP54

When ambient conditions need to be documented extremely accurately and securely, for example in a laboratory, the testo 176 P1 is the right data logger. It has an internal absolute pressure sensor and connection possibilities for two external temperature/humidity probes.

An integrated dewpoint calculation makes it universally applicable. The free ComSoft Basic software allows fast programming and easy data analysis.

## Technical data / Accessories

### testo 176 P1

testo 176 P1, 5-channel pressure, temperature and humidity data logger with internal sensor (absolute pressure) and external sensor connections (NTC/capacitive humidity sensor) incl. wall holder, lock, battery and calibration protocol

Part no. 0572 1767



#### General technical data

Channels	1 x internal, 2 probes external, 4 external channels (temperature/humidity)
Battery type	1 x Lithium (TL-5903)
Battery life	8 years (15 min. measuring cycle, +25 °C)
Operating temperature	-20 to +70 °C
Storage temperature	-40 to +85 °C
Dimensions	103 x 63 x 33 mm
Weight	230 g
Protection class	IP54
Measuring rate	1 s to 24 h (freely selectable, for online measurement 2 s to 24 h)
Memory	2 mio. measurement values
Interface	Mini USB, SD card slot

#### Sensor types

	NTC	Testo humid. sensor, cap.	Absolute pressure sensor
Measuring range	-20 to +70 °C	0 to 100 %RH*	600 to 1100 mbar
Accuracy ±1 digit	±0.2 °C (-20 to +70 °C) ±0.4 °C (remaining range)	dependent on probe selected	±3 mbar (0 to +50 °C)
Resolution	0.1 °C	0.1 %RH	1 mbar

\* Not for condensing atmospheres. For continuous applications in high humidity (>80 %RH at ≤30 °C for >12 h, >60 %RH at >30 °C for >12 h), please contact us via our website.



Lateral connection of Mini USB cable and SD card



Probe connection at lower end of housing for two temperature/humidity probes







Large, clear display for showing measurement values

## Accessories

Accessories for measuring instrument	Part no.
Mobile printer for data loggers testo 175/176/184	0572 0576
Wall holder (black) for testo 176	0554 1703
Cable for connecting the data loggers testo 175 and testo 176 to the PC, Mini-USB to USB	0449 0047
SD card - for collecting the measurement data from the data loggers testo 175 and testo 176; 2 GB; application range to -20 °C	0554 8803
Battery for testo 176 -1 x TL-5903 AA cell	0515 1760
ComSoft Basic, Basic software for programming and readout of Testo data loggers; graphic and tabular measurement value presentation as well as export function (if free download with registration not desired)	0572 0580
ComSoft Professional, Pro software incl. data archiving	0554 1704
ComSoft CFR 21 Part 11, Software for requirements according to CFR 21 Part 11 for Testo data loggers	0554 1705
ISO calibration certificate temperature temperature probe; calibration points -18 °C; 0 °C; +40 °C per channel/instrument	0520 0153
DAkkS calibration certificate temperature temp. data logger; cal. points -20°C; 0°C; +60°C; per channel/instrument	0520 0261
ISO calibration certificate humidity calibration points 11.3 %RH and 75.3 %RH at +25 °C/+77 °F; per channel/instrument	0520 0076
DAkkS calibration certificate humidity humidity probe; cal. points 11.3 %RH and 75.3 %RH at +25 °C; per channel/instrument	0520 0246
ISO calibration certificate pressure accuracy 0.1 to 0.6 (% of fsv), 5 points distributed over meas. range	0520 0025
DAkkS calibration certificate/pressure diff. and pos. pressure; 11 measuring points distributed over the instr. meas. range	0520 0215

## Probes

Probe type	Dimensions Probe shaft/probe shaft tip	Measuring range	Accuracy	Part no.
<b>Humidity/temperature probes</b>				
Humidity/temperature probe 12 mm		-20 to +70 °C 0 to 100 %RH	±0.3 °C ±2 %RH at +25 °C (2 to 98 %RH) ±0.03 %RH/K ± 1 digit	0572 6172
Humidity/temperature probe 4 mm		0 to +40 °C 0 to 100 %RH	±0.3 °C ±2 %RH at +25 °C (2 to 98 %RH) ±0.08 %RH/K ± 1 digit	0572 6174
Plug-in humidity/temperature probe 12 mm		-30 to +50 °C 0 to 100 %RH	±0.3 °C ±2 %RH at +25 °C (2 to 98 %RH)	0572 2151
Wall surface temperature probe		-50 to +80 °C	±0.5 °C (-40 to -25 °C) ±0.2 °C (-25 to +80 °C)	0628 7507

### CMI BELGIUM

Avenue de Ramelot 3  
B - 1480 Saintes (Sint Renelde)  
Tel : +32 (0)2 531 11 21  
info@cmitest.com

### CMI THE NETHERLANDS

Luchthavenweg 81  
NL – 5657 EA Eindhoven  
Tel : +31 (0)402 88 87 57  
infonl@cmitest.com

### CMI FRANCE

Ecoparc d'Affaires  
F- 41210 Neung-sur-Beuvron  
Tel : +33 (0)2 54 95 70 95  
infofr@cmitest.com

Agence Rhône Alpes :  
F- 26160 La Bégude-de-Mazenc  
Tel : +33 (0)4 75 54 57 26



www.cmitest.com