



Data sheet
testo 417



Vane anemometer

testo 417 – With built-in vane

Measurement of flow velocity, volume flow and temperature

Recognition of flow direction

Point and timed mean value calculation

Max./min. values

Hold button for freezing measurement value

Display illumination

Auto-off function



testo 417 is a compact, large-area anemometer with a built-in flow velocity / temperature vane. It measures flow velocity, volume flow and temperature. Thanks to the integrated measurement with the 100 mm vane, it is ideally suited for measurements at air input and output vents. The flow direction, i.e. blowing or sucking flow, is visible in the display. The optimum funnel set additionally allows measurements on ventilation grilles and disc outlets.

The volume flow is directly shown in the display. For the purposes of volume flow calculation, the duct area can be easily entered into the testo 417. In addition to this, the instrument can be switched over to display the current temperature.

Timed and point mean value calculation provide information on the average volume flow, flow velocity and temperature measurement value. The Hold function allows the current measurement value to be frozen in the display, min./max. values are also displayed at the press of a button.

Technical data / Accessories

testo 417

testo 417 vane anemometer with integrated 100 mm vane incl. temperature measurement, battery and calibration protocol

Part no. 0560 4170



General technical data

Storage temperature	-40 to +70 °C
Operating temperature	0 to +50 °C
Battery type	9V block battery, 6F22
Battery life	50 h
Weight	230 g
Dimensions	277 x 105 x 45 mm
Housing material	ABS

Sensor types

	NTC	Vane	Volume flow
Measuring range	0 to +50 °C	+0.3 to +20 m/s	0 to +99999 m ³ /h
Accuracy ±1 digit	±0.5 °C	±(0.1 m/s +1.5% of m.v.)	
Resolution	0.1 °C	0.01 m/s	0.1 m ³ /h (0 to +99.9 m ³ /h) 1 m ³ /h (+100 to +99999 m ³ /h)

Accessories for measuring instrument

Part no.

Accessories for measuring instrument	Part no.
Case for measuring instrument and probes	0516 0191
testovent 417 funnel set for plate outlets (Ø 200 mm) and funnel for ventilator (330 x 330 mm)	0563 4170
Flow straightener testovent 417	0554 4172
9V rech. battery for instrument instead of battery	0515 0025
DAkKS calibration certificate velocity, hot wire, vane anemometer; calibration points 0.5; 1; 2; 5; 10 m/s	0520 0244
ISO calibration certificate velocity, hot wire, vane anemometer, Pitot tube; calibration points 1; 2; 5; 10 m/s	0520 0004
ISO calibration certificate velocity, hot wire, vane anemometer, Pitot tube; calibration points 5; 10; 15; 20 m/s	0520 0034
ISO calibration certificate velocity, hot wire, vane anemometer; calibration points 0.3; 0.5; 0.8; 1.5 m/s	0520 0024

CMI BELGIUM

Avenue de Ramelot 3
B - 1480 Saintes (Sint Renelde)
Tel : +32 (0)2 531 11 21
info@cmitest.com

CMI THE NETHERLANDS

Luchthavenweg 81
NL - 5657 EA Eindhoven
Tel : +31 (0)402 88 87 57
info@cmitest.com

CMI FRANCE

Ecoparc d'Affaires
F- 41210 Neung-sur-Beuvron
Tel : +33 (0)2 54 95 70 95
info@cmitest.com

Agence Rhône Alpes :
F- 26160 La Bégude-de-Mazenc
Tel : +33 (0)4 75 54 57 26



www.cmitest.com