



Cleanroom Management International  
*Groupe Trescal*

# PLUG AND PLAY TEMPERATURE MONITORING



# LogTag®

USRIC-8  
Single-Use PDF USB  
Temperature Logger



The LogTag® USRIC-8 is a single-use, cost effective and reliable temperature recorder. It measures and stores real-time temperature range readings from -30°C to +60°C (from -22°F to +140°F).


The LogTag® USRIC-8 combines all the features of an advanced temperature recorder with an 8,000-log memory. It has a shelf life of up to two years before configuration (in standard hibernation mode), and a 6-month fixed battery operating life.

Data from LogTag® USRIC-8 downloaded using the LogTag® Xpress can be uploaded and viewed in LogTag® Online without the need for creating an account.


Scan the QR code to get started.

## Accessories

---



*Wall Mount*  
Not Included



*Protective Enclosure*  
Not Included

# Features

---



Records temperature from  $-30^{\circ}\text{C}$  to  $+60^{\circ}\text{C}$ .



Data is viewable in LogTag® Online without the need for an account.\*



Automatic generation of a PDF, CSV, LogTag® Data report without special software.



Six user-configurable alarms.



Up to 8,000 recordings, enough for the longest trip.



Comprehensive customization options including alert settings, sample interval and trip duration.



Built-in integrated USB connector without the need for a separate Interface Cradle.



Fixed battery provides 2 years storage, followed by 6 months normal use.



Push-to-start button with optional delay or a specific time and date.

\*Uploading files to LogTag® Online is enabled by default on new installations of LogTag® Xpress (version 1.2.2 onwards).

# Applications

---



Transportation



Perishables Transport



Produce Transport



Pharmaceutical Transport



Vaccines Transport

# Specifications

<b>Product Model</b>	USRIC-8
<b>Sensor Measurement Range</b>	-30°C to +60°C (-22°F to +140°F).
<b>Operating Temperature Range</b>	-30°C to +60°C (-22°F to +140°F).
<b>Storage Temperature Range</b>	0°C to +40°C (32°F to +104°F).
<b>Rated Temperature Reading Accuracy</b>	Better than $\pm 0.5^{\circ}\text{C}$ ( $\pm 0.9^{\circ}\text{F}$ ) for $-5^{\circ}\text{C}$ to $+30^{\circ}\text{C}$ ( $23^{\circ}\text{F}$ to $+86^{\circ}\text{F}$ ). $\pm 0.8^{\circ}\text{C}$ ( $\pm 1.5^{\circ}\text{F}$ ) or better for measurements in other areas of rated range. <i>Actual performance is typically much better than the rated values.</i> <i>Accuracy figures can be improved by recalibration.</i>
<b>Rated Temperature Reading Resolution</b>	< 0.1°C/F <i>LogTag Analyzer® currently displays to one decimal place of °C or °F. The native resolution is what is stored in the LogTag®.</i>
<b>Sensor Reaction Time</b>	Typically less than 5 minutes (T90) in moving air (1m/s).
<b>Recording Capacity</b>	8,001 temperature readings. 27 days @ 5min logging, 80 days @ 15min logging.
<b>Sampling Interval</b>	Configurable from 1 minute to 18 hours.
<b>Logging Start Options</b>	Push button start or specific date & time.
<b>Recording Indication</b>	Flashing 'OK' indicator / flashing 'ALERT' indicator.
<b>Alarms</b>	6 user-configurable alarms.
<b>Download Time</b>	Typically in less than 20 seconds from time of insertion to availability of PDF report. Typically less than 10 seconds from time of insertion to availability of LTD file in LogTag® Analyzer (if configured).
<b>Environmental</b>	IEC 60529: IP64 with USB cap fitted.
<b>Power Source</b>	CR2032 3V LiMnO <sub>2</sub> Battery (Fixed).
<b>Battery Life</b>	2 years storage, followed by 6 months normal use.
<b>Real Time Clock</b>	Built-in real time clock. Rated accuracy $\pm 25\text{ppm}$ @ $25^{\circ}\text{C}$ (equivalent to 2.5 seconds/day). Rated temperature coefficient is $-0.034 \pm 0.006\text{ppm}/^{\circ}\text{C}$ (i.e typically +/- 0.00294 seconds/day/°C).
<b>Connection Interface</b>	USB 2.0, A-type plug.
<b>Software</b>	PDF Reader, LogTag® Analyzer 2.5 or higher, LogTag Xpress, LogTag Online
<b>Size</b>	93mm(H) x 54.5mm(W) x 8.6mm(T) including protective USB cap.
<b>Weight</b>	31g.
<b>Case Material</b>	Polycarbonate.



#### CMI BELGIUM

Avenue de Ramelot 3  
B - 1480 Saintes (Sint Renelde)  
Tel : +32 (0)2 531 11 21  
info@cmitest.com

#### CMI THE NETHERLANDS

Luchthavenweg 81  
NL - 5657 EA Eindhoven  
Tel : +31 (0)402 88 87 57  
infoln@cmitest.com

#### CMI FRANCE

Ecoparc d'Affaires  
F- 41210 Neung-sur-Beuvron  
Tel : +33 (0)2 54 95 70 95  
infofr@cmitest.com

Agence Rhône Alpes :  
F- 26160 La Bégude-de-Mazenc  
Tel : +33 (0)4 75 54 57 26



[www.cmitest.com](http://www.cmitest.com)